

MachineryMate™ handheld vibration meter

MAC200



Wilcoxon's handheld vibration meter helps find machine faults before they impact operation or cause catastrophic failures. The MAC200 can increase productivity and lower maintenance costs by identifying vibration problems and bearing conditions in early and late stages of failure. The simple, easy to use meter records, analyzes and displays vibration signals and comes with built-in band filters for unbalance, misalignment, and looseness. The low Hertz range allows readings on machinery running as slow as 120 RPM.

The meter assists in condition monitoring for industries including commercial and industrial HVAC, food processing, packing, petrochemical, pulp and paper, power plants and utilities. The MAC200 is a cost-effective tool with high level functionality and capability for a comprehensive picture of machinery health.

Key features

- Built-in ISO alarms
- Easily identify bearing problems with BDU reading
- 100 and 800 line FFT spectrum
- Ruggedized IP67 case
- Full color OLED display
- High performance accelerometer with stinger

Certifications



Note: Due to continuous process improvement, specifications are subject to change without notice. This document is cleared for public release.

Wilcoxon Sensing Technologies
20511 Seneca Meadows Parkway
Germantown, MD 20876
info@wilcoxon.com

Tel: (301) 330 8811
Fax: (301) 330 8873
www.wilcoxon.com

Wilcoxon Sensing Technologies
An Amphenol Company

MachineryMate™ handheld vibration meter

MAC200



SPECIFICATIONS

	English	Metric
Size	7.95 x 2.36 x 1"	20 x 6 x 2.6 cm
Weight (excluding magnet)	9.8 oz	280 grams
Environmental		
Water	IP 67 waterproof	IP 67 waterproof
Operating temperature	+32 to +122° F	0 to +50° C
Storage temperature	-4 to +158° F	-20 to +70° C
Power supply	2x AA batteries	2x AA batteries
Battery life	50 hours normal use	50 hours normal use
Frequency ranges		
ISO	120 - 60,000 CPM	2 Hz - 1 kHz
BDU	60 - 900,000 CPM	1 - 15 kHz
Max frequency resolution	1.25 Hz at 800 lines FFT setting	1.25 Hz at 800 lines FFT setting
Displayed amplitude units		
Acceleration	g	g
Bearing damage	BDU	BDU
Velocity	in/sec	mm/sec
Displayed frequency units	Hz	CPM or RPM
Input range	±50 g	490 m/sec ²
Dynamic range, 0.01 g resolution	72 dB	72 dB
VA bands	Auto set-up	Auto set-up
Accelerometer connection	internal sensor	internal sensor
Display	OLED full color, high contrast	OLED full color, high contrast
Selectable languages	English (default), Spanish, Portuguese, French, Italian, Turkish, Chinese, Japanese and Korean	

Contact

Wilcoxon Sensing Technologies

20511 Seneca Meadows Parkway
Germantown MD 20876, USA

Tel: +1 301 330 8811
Fax: +1 301 330 8873

info@wilcoxon.com

www.wilcoxon.com

Accessories supplied:

- MAC002 protective boot with magnets
- MAC003 carrying case with insert
- Extended stinger

Note: Due to continuous process improvement, specifications are subject to change without notice.
This document is cleared for public release.

Wilcoxon Sensing Technologies
20511 Seneca Meadows Parkway
Germantown, MD 20876
info@wilcoxon.com

Tel: (301) 330 8811
Fax: (301) 330 8873
www.wilcoxon.com

Wilcoxon Sensing Technologies
An Amphenol Company